

DC Pass

# Power Splitter/Combiner

## ZN2PD-63-S+

2 Way-0° 50Ω 1800 to 6000 MHz



Generic photo used for illustration purposes only

CASE STYLE: VVV180

Connectors	Model
SMA	ZN2PD-63-S+

**+RoHS Compliant**

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Maximum Ratings


Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	10W max.
Internal Dissipation	0.25W max.
DC Current	700 mA (350mA for each port)

Permanent damage may occur if any of these limits are exceeded.

### Coaxial Connections

SUMPORT	S
PORT 1	1
PORT 2	2

### Outline Drawing



### Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
1.80	1.75	.66	.125	1.675	.125	.125
45.72	44.45	16.76	3.18	42.55	3.18	3.18

H	J	K	L	M	wt
1.625	.31	.63	1.13	.88	grams
41.28	7.87	16.00	28.70	22.35	65.2

### Features

- wide frequency band, 1800-6000 MHz
- high isolation, 19 dB min.
- very good VSWR, 1.22:1 typ.

### Applications

- PCS
- WIMAX
- satellite up & down links
- line of sight links




### Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) ABOVE 3.0 dB		PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)	VSWR (:1)			
	Typ.	Min.	Typ.	Max.	Max.	Max.	S		OUT	
$f_L$ - $f_U$							Typ.	Max.	Typ.	Max.
1800-6000	24	19	0.4	0.7	4	0.3	1.22	1.55	1.18	1.30


### Typical Performance Data

Frequency (MHz)	Total Loss <sup>1</sup> (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
1800.00	3.33	3.31	0.02	21.91	0.54	1.42	1.16	1.18
2000.00	3.31	3.29	0.02	25.15	0.61	1.32	1.16	1.17
2200.00	3.30	3.27	0.03	26.23	0.66	1.22	1.15	1.16
2400.00	3.30	3.27	0.03	25.00	0.72	1.12	1.13	1.14
2600.00	3.31	3.28	0.03	23.60	0.80	1.03	1.11	1.12
3000.00	3.35	3.31	0.04	22.50	0.96	1.12	1.12	1.13
3400.00	3.37	3.33	0.04	24.13	1.01	1.19	1.13	1.14
3800.00	3.38	3.32	0.05	28.69	1.11	1.17	1.12	1.12
4200.00	3.38	3.32	0.06	31.64	1.20	1.13	1.09	1.07
4600.00	3.40	3.34	0.06	27.68	1.27	1.14	1.07	1.07
5000.00	3.45	3.39	0.07	25.60	1.34	1.15	1.09	1.11
5400.00	3.49	3.41	0.08	25.15	1.45	1.10	1.11	1.12
5600.00	3.50	3.42	0.08	24.70	1.47	1.06	1.13	1.12
5800.00	3.49	3.41	0.08	23.45	1.54	1.03	1.12	1.12
6000.00	3.50	3.41	0.09	21.28	1.62	1.09	1.11	1.11

1. Total Loss = Insertion Loss + 3dB splitter loss.



### electrical schematic



### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.  
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.  
 C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



# 2 Way-0° Power Splitter/Combiner

# ZN2PD-63-S+

## Typical Performance Data

FREQUENCY (MHz)	TOTAL LOSS <sup>1</sup> (dB)		AMPLITUDE UNBALANCE (dB)	ISOLATION (dB)	PHASE UNBALANCE (deg.)	FREQUENCY (MHz)	VSWR (:1)		
	S-1	S-2					S	1	2
1800	3.33	3.31	0.02	21.91	0.54	1800	1.42	1.16	1.18
1900	3.32	3.30	0.02	23.60	0.57	1900	1.37	1.17	1.18
2000	3.31	3.29	0.02	25.15	0.61	2000	1.32	1.16	1.17
2100	3.30	3.28	0.02	26.11	0.64	2100	1.27	1.15	1.17
2200	3.30	3.27	0.03	26.23	0.66	2200	1.22	1.15	1.16
2300	3.30	3.27	0.02	25.80	0.68	2300	1.17	1.13	1.15
2400	3.30	3.27	0.03	25.00	0.72	2400	1.12	1.13	1.14
2500	3.30	3.28	0.03	24.26	0.77	2500	1.07	1.12	1.13
2600	3.31	3.28	0.03	23.60	0.80	2600	1.03	1.11	1.12
2700	3.32	3.29	0.03	23.07	0.82	2700	1.01	1.10	1.11
2800	3.33	3.29	0.03	22.73	0.86	2800	1.05	1.11	1.11
2900	3.33	3.30	0.03	22.54	0.92	2900	1.08	1.11	1.12
3000	3.35	3.31	0.04	22.50	0.96	3000	1.12	1.12	1.13
3200	3.36	3.32	0.04	22.97	0.96	3200	1.16	1.13	1.14
3400	3.37	3.33	0.04	24.13	1.01	3400	1.19	1.13	1.14
3600	3.38	3.33	0.05	26.10	1.06	3600	1.19	1.14	1.13
3800	3.38	3.32	0.05	28.69	1.11	3800	1.17	1.12	1.12
4000	3.38	3.32	0.05	31.34	1.14	4000	1.15	1.12	1.09
4200	3.38	3.32	0.06	31.64	1.20	4200	1.13	1.09	1.07
4400	3.39	3.33	0.06	29.57	1.21	4400	1.14	1.08	1.06
4600	3.40	3.34	0.06	27.68	1.27	4600	1.14	1.07	1.07
4800	3.43	3.36	0.07	26.41	1.32	4800	1.16	1.09	1.09
5000	3.45	3.39	0.07	25.60	1.34	5000	1.15	1.09	1.11
5200	3.48	3.40	0.07	25.38	1.38	5200	1.13	1.12	1.12
5400	3.49	3.41	0.08	25.15	1.45	5400	1.10	1.11	1.12
5600	3.50	3.42	0.08	24.70	1.47	5600	1.06	1.13	1.12
5800	3.49	3.41	0.08	23.45	1.54	5800	1.03	1.12	1.12
6000	3.50	3.41	0.09	21.28	1.62	6000	1.09	1.11	1.11

<sup>1</sup>Total Loss = Insertion Loss + 3dB Splitter Loss



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site








The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)

IF/RF MICROWAVE COMPONENTS


REV. OR  
ZN2PD-63-S+  
1/17/2019  
Page 1 of 1

## Typical Performance Curves



## Outline Dimensions

VVV180



CASE#	A	B	C	D	E	F	G	H	J	K	L
VVV180	1.80 (45.72)	1.75 (44.45)	.66 (16.76)	.125 (3.18)	1.675 (42.55)	.125 (3.18)	.125 (3.18)	1.625 (41.28)	.31 (7.87)	.63 (16.00)	1.13 (28.70)

CASE#	M	WT.GRAMS
VVV180	.88 (22.35)	65.2

Dimensions are in inches (mm). Tolerances: 2 Pl.  $\pm .03$ ; 3 Pl.  $\pm .015$

### Notes:

1. Case material: Aluminum alloy.
2. Case finish:  
For RoHS Case Styles: Clear chemical conversion coating, non-chrome or trivalent chrome based.
3. Refer to the individual model data sheet for the type of connectors available.

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

<b>Specification</b>	<b>Test/Inspection Condition</b>	<b>Reference/Spec</b>
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I