

SAI Global File #004008

Burlington, Ontario, Canada

824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

# **Safety Data Sheet**

#### **Section 1: Identification**

#### **Product Identifier and Other Means of Identification**

Product Name: Isopropyl Alcohol Electronics Cleaner

Other Means of Identification: 824-a Related Part # 824-450G, 824-450GCA

#### **Recommended Use and Restriction on Use**

Use: Cleaner for electronics

Uses Advised Against: Not for use on monitor screens or glass with anti-glare coatings

# **Details of Manufacturer or Importer**

#### Manufacturer

MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

# +1-800-340-0772

FAX +1-800-340-0773

E-MAIL support@mgchemicals.com

WEB www.mgchemicals.com

MG Chemicals (Head Office)

9347-193 Street

Surrey, British Columbia V4N 4E7

**CANADA** 

+1-905-331-1396

FAX +1-905-331-2682

E-MAIL info@mqchemicals.com

**E-MAIL** (Competent Person): sds@mgchemicals.com

# **Emergency Phone Number**

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents) USA or CANADA—Call CHEMTREC at +1-800-424-9300

For emergencies involving the transport of dangerous goods; 24/7 service CANADA—Call CANUTEC collect at +1-613-996-6666 or \*666 on cellular phones



SAI Global File #004008

Burlington, Ontario, Canada

824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

# Section 2: Hazard(s) Identification

#### **Classification of Hazardous Materials**

# **GHS Categories**

| Criteria                                       | Category      | Signal<br>Word | Pictograms   |
|--|---------------|----------------|--------------|
| Flammable Aerosol                              | 2             | Warning        | Flame        |
| Gas Under Pressure                             | Liquefied Gas | Warning        | Gas Cylinder |
| Eye Irritation                                 | 2A            | Warning        | Exclamation  |
| Specific Target Organ Toxicity Single Exposure | 3             | Warning        | Exclamation  |

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity categories do not allow comparisons between classes.

# **Label Elements**

| Signal Word | WARNING  |
|-------------|--|
| Pictograms  | Hazard Statements  |
|             | H223: Flammable aerosol                                  |
|             | H280: Contains gas under pressure; may explode if heated |
| ^           | H319: Causes serious eye irritation                      |
| !           | H336: May cause drowsiness or dizziness                  |

Section continued on the next page



SAI Global File #004008

Burlington, Ontario, Canada

# 824-A

# ISOPROPYL ALCOHOL ELECTRONICS CLEANER

#### Continued...

| Prevention            | Precautionary Statements   |
|-----------------------|--|
| P102                  | Keep out of reach of children.   |
| P210                  | Keep away from heat/sparks/open flames/hot surfaces. No smoking.   |
| P211                  | Do not spray on an open flame or other ignition source.  |
| P251                  | Do not pierce or burn, even after use.   |
| P261                  | Avoid breathing mist/vapors/spray.   |
| P271                  | Use only outdoors or in a well-ventilated area.  |
| P280                  | Wear eye protection.   |
| P264                  | Wash hands thoroughly after handling.  |
| Response              | Precautionary Statements   |
| P305 + P351 +<br>P358 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337 + P313           | If eye irritation persists: Get medical advice/attention.  |
| P304+ P340            | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P312                  | Call a POISON CENTER/doctor if you feel unwell.  |
| Storage               | Precautionary Statements   |
| P410 + P412           | Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].   |
| P403                  | Store in a well-ventilated place.  |
| P405                  | Store locked up.   |
| Disposal              | Precautionary Statements   |
| P501                  | Dispose of contents/container in accordance to local/regional/national/international regulations.                                |

Section continued on the next page



SAI Global File #004008

Burlington, Ontario, Canada

# 824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

# **Hazards Not Otherwise Classified**

| HCS2012<br>Criteria  | Hazard Statements/Precautionary Statement             | Signal<br>Word | Pictograms |
|----------------------|---|----------------|------------|
| Simple<br>Asphyxiant | May displace oxygen and cause rapid suffocation.      | Warning        | None       |
| Defats skin          | Repeated exposure may cause skin dryness or cracking. | None           | None       |

# **Section 3: Composition/Information on Ingredients**

| CAS #   | Chemical Name             | %(weight) |
|---------|---------------------------|-----------|
| 67-63-0 | propan-2-ol <sup>a)</sup> | 75%       |
| 75-37-6 | 1,1-difluoroethane        | 25%       |

a) Commonly known as isopropyl alcohol (IPA)



SAI Global File #004008

Burlington, Ontario, Canada

# 824-A

# ISOPROPYL ALCOHOL ELECTRONICS CLEANER

| Section 4: First-Aid Mea | sures   |
|--------------------------|---|
| Exposure Condition       | GHS Code: Precautionary Statement   |
| IF IN EYES               | P305 + P351+ P338, P337 + P313  |
| Immediate Symptoms       | redness, irritation, tearing  |
| Response                 | Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
|                          | If eye irritation persists: Get medical advice/attention.   |
| IF INHALED               | P304 + P340, P312   |
| Immediate Symptoms       | dizziness, drowsiness, cough, headaches, weakness, unconsciousness  |
| Response                 | Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing.                   |
|                          | If feeling unwell: Call a POISON CENTRE/doctor.   |
| IF SWALLOWED             | P301 + P330, P331, P312<br>(Not a likely route of exposure under normal use)                                    |
| Immediate Symptoms       | Low toxicity: nausea, headache, dizziness, drowsiness, weakness, abdominal pain, unconsciousness                |
| Response                 | Rinse mouth. Do NOT induce vomiting.  |
|                          | If feeling unwell: Call a POISON CENTRE/doctor.   |
| IF ON SKIN (or hair)     | P302 + P353   |
| Immediate Symptoms       | Low toxicity: mild irritation   |
| Response                 | Rinse skin with water or shower.  |



SAI Global File #004008 Burlington, Ontario, Canada

824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

# **Section 5: Fire-Fighting Measures**

**Extinguishing Media** Use extinguishing media suitable for surrounding materials.

Use water spray to cool containers.

**Specific Hazards** Aerosols containers may erupt with force at temperatures

above 50 °C [122 °F].

Produces irritating and toxic fumes in fires or in contact with

hot surfaces.

The vapors are heavier than air and may accumulate in lowlying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.

**Combustion Products** Produces carbon oxides (CO, CO<sub>2</sub>) halogenated compounds,

and hydrogen fluoride (HF).

**Fire-Fighter** Wear self-contained breathing apparatus and full fire-fighting

turn-out gear.

#### **Section 6: Accidental Release Measures**

**Personal Protection** See personal protection recommendations in Section 8.

**Precautions for** 

Response

Avoid breathing the mist/spray/vapors. Remove or keep away

all sources of extreme heat or open flames.

**Environmental Precautions** 

Avoid releasing to the environment. Prevent spill from entering

drains and waterways.

**Containment Methods** Not applicable

**Cleaning Methods** Collect liquid in a sealable, solvent-resistant container. Sprinkle

inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the

last traces of residue.

**RECOMMENDATION:** Use a grounded stainless steel or carbon

steel waste container.

**Disposal Methods** Dispose of spill waste according to Section 13.



SAI Global File #004008

Burlington, Ontario, Canada

824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

#### Section 7: Handling and Storage

**Prevention** Keep out of reach from children.

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce

or burn, even after use.

Avoid breathing mist/spray/vapors. Use only outdoors or in a well-

ventilated area.

**Handling** Wear eye protection.

Wash hands thoroughly after handling.

**Storage** Protect from sunlight. Do not expose to temperatures exceeding 50 °C

[122 °F].

Store in a well-ventilated place.

Store locked up.

#### **Section 8: Exposure Controls/Personal Protection**

# **Substances with Occupational Exposure Limit Values**

| Chemical Name      | Country                  | Long Term Exposure Limits (PEL) | Short Term<br>Exposure Limits<br>(STEL) |
|--------------------|--------------------------|---------------------------------|---|
| propan-2-ol        | ACGIH<br>U.S.A. OSHA PEL | 200 ppm (TWA)<br>400 ppm        | 400 ppm<br>not established              |
|                    | Canada AB                | 200 ppm                         | 400 ppm                                 |
|                    | Canada BC                | 200 ppm                         | 400 ppm                                 |
|                    | Canada ON                | 200 ppm                         | 400 ppm                                 |
|                    | Canada QC                | 400 ppm                         | 500 ppm                                 |
| 1,1-difluoroethane | ACGIH                    | Not established                 | Not established                         |
|                    | U.S.A. OSHA PEL          | Not established                 | Not established                         |
|                    | Canada                   | Not established                 | Not established                         |

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Section continued on the next page



SAI Global File #004008

Burlington, Ontario, Canada

#### 824-a

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

# **Engineering Controls**

Ventilation Keep airborne concentrations below the occupational exposure

limits (OEL).

# **Personal Protective Equipment**

Eye protection Wear appropriate protective eyeglasses or chemical safety

goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection

(side shields).

Skin Protection Wear appropriate protective clothing to prevent skin contact.

**RECOMMENDATION:** Use of protective gloves in butyl rubber,

nitrile rubber, or other chemically resistant gloves.

**Respiratory Protection** If exposed to mist, wear respirator such as a half-mask

respirator.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3.

The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed

plastic bags when not being used.

# **General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

824-A

#### **Quality System Certified to ISO 9001:2008**

SAI Global File #004008

Burlington, Ontario, Canada

ISOPROPYL ALCOHOL ELECTRONICS CLEANER

# Section 9: Physical and Chemical Properties

| Physical State            | Liquid in aerosol<br>format | Lower Flammability<br>Limit  | 2%                     |
|---------------------------|-----------------------------|------------------------------|------------------------|
| Appearance                | Colorless                   | Upper Flammability<br>Limit  | 12%                    |
| Odor                      | Alcohol-like                | Vapor Pressure<br>@20°C      | 4.2 kPa<br>[32 mmHg]   |
| Odor Threshold            | Not available               | Vapor Density                | ≥1.6                   |
| рН                        | Not available               | Specific Gravity<br>@25 °C   | 0.785                  |
| Freezing/Melting<br>Point | -88 °C<br>[-126 °F]         | Solubility in<br>Water       | Fully miscible         |
| <b>Boiling Point</b>      | ≥81.8 °C<br>[≥179 °F]       | Partition<br>Coefficient     | Not available          |
| Flash Point a)            | 12 °C<br>[54 °F]            | Auto-ignition<br>Temperature | 425 °C<br>[797 °F]     |
| Evaporation<br>Rate       | 1.5<br>(ButAc = 1)          | Decomposition<br>Temperature | Not available          |
| Flammability (solid, gas) | Not applicable              | Viscosity<br>@20 °C          | 2.4 mPa·s<br>[3.1 cSt] |

a) Closed cup value



SAI Global File #004008 Burlington, Ontario, Canada

824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

# **Section 10: Stability and Reactivity**

**Reactivity** Not available

**Chemical** Chemically stable at normal temperatures and pressures

Stability

**Conditions to** Temperatures above 50 °C [122 °F], open flames, and incompatible

**Avoid** substances

**Incompatibilities** Strong oxidizing agents, strong acids, alkali and alkali earth metals,

halogenated compounds, aluminum at temperatures ≥49 °C

[>120 °F]

Polymerization Will not occur

**Decomposition** Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

#### **Section 11: Toxicological Information**

#### **Summary of Effects and Symptoms by Routes of Exposure**

**Eyes** Causes serious eye redness, irritation, or tearing.

**Skin** Low toxicity: mild irritation

**Inhalation** May cause drowsiness or dizziness. Excessive exposure may cause

cough, headaches, weakness, and unconsciousness.

**Ingestion** Low toxicity. See inhalation symptoms.

**Chronic** Prolonged or repeated exposure may defat skin and cause skin

dryness and cracking, and local redness and discomfort.

# **Acute Toxicity (Lethal Exposure Concentrations)**

| Chemical Name      | LD50        | LD50         | LC50       |
|--------------------|-------------|--------------|------------|
|                    | oral        | dermal       | inhalation |
| isopropyl alcohol  | 3 600 mg/kg | 12 800 mg/kg | 16 000 ppm |
|                    | Rat         | Rabbit       | 8 h Rat    |
| 1,1-difluoroethane | Not         | Not          | 1 500 g/m³ |
|                    | available   | available    | 4 h Rat    |

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier (M)SDSs were also consulted.

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

824-a

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

Skin corrosion/irritation Based on available data, the classification criteria are not

met. Propan-2-ol causes mild skin irritation based on

Draize tests on rabbits.

Serious eye Propan-2-ol causes moderate to severe eye irritation damage/irritation

based on Draize tests on rabbits

Sensitization Based on available data, the classification criteria are not

(allergic reactions) met.

Carcinogenicity None of the ingredients are classified or listed as a

carcinogen by IARC, ACGIH, CA Prop 65, or NTP. (risk of cancer)

Mutagenicity Based on available data, the classification criteria are not

met.

(risk of heritable genetic effects)

**Reproductive Toxicity** (risk to sex functions)

Based on available data, the classification criteria are not

Teratogenicity

Based on available data, the classification criteria are not (risk of fetus malformation)

met.

STOT-single exposure Propan-2-ol can affect the central nervous system by

inhalation causing drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not

met.

Aspiration hazard Based on available data, the classification criteria are not

met. There are no category 1 components.

# **Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<a href="http://echa.europa.eu">http://echa.europa.eu</a>), and other reliable sources.

Propan-2-ol is not classifiable as an environmental toxicant (with minimal LC50 of >100 mg/L).

Propan-2-ol is readily biodegradable and has a minimal LC50 96 h of 9 640 mg/L for Pimephales promelas (fathead minnow); an EC50 24 h of 5 102 mg/L Daphnia magna (water flea); and an EC50 72 h of >2 000 mg/L Desmodesmus subspicatus (green algae).

# **Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds.

Section continued on the next page



SAI Global File #004008

Burlington, Ontario, Canada

# 824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

# **Chronic Ecotoxicity**

Available toxicity data does not meet classification thresholds.

#### **Biodegradability**

The constituents are volatile and readily biodegradable.

#### Other Effects

Volatile Organic Content (VOC) = 75% (589 g/L)

# Section 13: Disposal Considerations

Dispose of contents in accordance with all local, regional, national, and international regulations.

#### **Section 14: Transport Information**

#### Ground

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations); USA DOT 49 CFR (Parts 100 to 185) Regulations.

#### **Limited Quantity**



**UN number**: UN1950

Shipping Name: AEROSOL,

flammable **Class: 2.1** 

Packing Group: Not applicable

Marine Pollutant: No

#### Air

#### Refer to ICAO-IATA Dangerous Goods Regulations.

#### **Limited Quantity** Max Net Qty/Pkg =30 kg Gross



**UN number**: UN1950 Shipping Name: AEROSOL,

flammable

**Class: 2.1** 

Packing Group: Not applicable

Marine Pollutant: No

Section continued on the next page

SAI Global File #004008

Burlington, Ontario, Canada

# 824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

#### Sea



**Limited Quantity** 



UN number: UN1950 Shipping Name: AEROSOL,

flammable **Class:** 2.1

Packing Group: Not applicable

Marine Pollutant: No

*Note:* Shipper must be appropriately <u>trained and certified</u> before involvement with the transport of dangerous goods.

# Section 15: Regulatory Information

#### Canada

#### **Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.

#### Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

#### **USA**

#### **Other Classifications**

#### **HMIS® RATING**

| HEALTH:              | * | 2 |
|----------------------|---|---|
| FLAMMABILITY:        |   | 3 |
| PHYSICAL HAZARD:     |   | 0 |
| PERSONAL PROTECTION: |   | · |

#### NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

Section continued on the next page



SAI Global File #004008

Burlington, Ontario, Canada

#### 824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product contains 75% propan-2-ol (CAS # 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, Sept 2, 2011 revision, USA).

This product does not contain any substances known to be listed in California.

#### **Europe**

**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

#### **Section 16: Other Information**

SDS Prepared by Michel Hachey

Date of Revision 26 October 2017

Supersedes 28 May 2014

Reason for Changes: Minor format revisions in with WHMIS 2015 and HCS 2012.

#### References

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page



SAI Global File #004008 Burlington, Ontario, Canada

# 824-A

#### ISOPROPYL ALCOHOL ELECTRONICS CLEANER

#### **Abbreviations**

ACGIH American Conference of Governmental Industrial Hygienists (USA)

EC50 Half maximal effective concentration EL50 Half maximal effective loading

NOELR No observable effect loading ratio

GHS Globally Harmonized System of Classification of Labeling of Chemicals

LC50 Lethal Concentration 50%

LCLo Lowest published lethal concentration

LD50 Lethal Dose 50%

PEL Permissible Exposure Limit STEL Short-Term Exposure Limit

TCLo Lowest published toxic concentration

TWA Time Weighted Average VOC Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: <a href="mailto:support@mgchemicals.com">support@mgchemicals.com</a>

Mailing Addresses Manufacturing & Support Head Office

1210 Corporate Drive 9347–193rd Street

Burlington, Ontario, Canada Surrey, British Columbia, Canada

L7L 5R6 V4N 4E7

Disclaimer

This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.