



# STTH20002TV


## TURBO 2 ULTRAFAST HIGH VOLTAGE RECTIFIER

### MAIN PRODUCT CHARACTERISTICS

$I_{F(AV)}$	Up to 2 x 120 A
$V_{RRM}$	200 V
$T_j$	150°C
$V_F$ (typ)	0.75 V
$t_{rr}$ (typ)	41 ns

### FEATURES AND BENEFITS

- Suited for SMPS
- Very Low Forward Losses
- Low recovery time
- High surge current capability
- Insulated:  
Insulating voltage=2500V<sub>RMS</sub>  
Capacitance = 55pF



### DESCRIPTION

Dual rectifier suited for welding equipment, high power industrial application.  
Packaged in Isotop, this device is intended for use in the secondary rectification of the applications.

### ABSOLUTE RATINGS (limiting values, per diode)

Symbol	Parameter	Value	Unit	
$V_{RRM}$	Repetitive peak reverse voltage	200	V	
$I_{F(RMS)}$	RMS forward voltage	170	A	
$I_{F(AV)}$	Average forward current $\delta = 0.5$	$T_c = 95^\circ\text{C}$ Per diode	100	A
		$T_c = 80^\circ\text{C}$ Per diode	120	
$I_{FSM}$	Surge non repetitive forward current	$t_p = 10\text{ms}$ sinusoidal	1000	A
$T_{stg}$	Storage temperature range	-55 to + 150	°C	
$T_j$	Maximum operating junction temperature	150	°C	

### Order Codes

Part Number	Marking
STTH20002TV1	STTH20002TV1

## THERMAL RESISTANCE

Symbol	Parameter	Maximum	Unit
$R_{th(j-c)}$	Junction to case	Per diode	0.52
		Total	0.31
$R_{th(c)}$	Coupling	0.1	$^{\circ}\text{C}/\text{W}$

When the diodes 1 and 2 are used simultaneously:

$$\Delta T_{j(\text{diode } 1)} = P(\text{diode } 1) \times R_{th(j-c)}(\text{Per diode}) + P(\text{diode } 2) \times R_{th(c)}$$

## STATIC ELECTRICAL CHARACTERISTICS (per diode)

Symbol	Parameter	Test conditions	Min.	Typ	Max.	Unit
$I_R^*$	Reverse leakage current	$T_j = 25^{\circ}\text{C}$	$V_R = V_{RRM}$		100	$\mu\text{A}$
		$T_j = 125^{\circ}\text{C}$		80	800	
$V_F^{**}$	Forward voltage drop	$T_j = 25^{\circ}\text{C}$	$I_F = 100\text{A}$		1.05	V
			$I_F = 200\text{A}$		1.20	
		$T_j = 150^{\circ}\text{C}$	$I_F = 100\text{A}$	0.75	0.85	
			$I_F = 200\text{A}$		1.05	

Pulse test: \*  $t_p = 5 \text{ ms}$ ,  $\delta < 2\%$

\*\*  $t_p = 380 \mu\text{s}$ ,  $\delta < 2\%$

To evaluate the conduction losses use the following equation:  $P = 0.65 \times I_{F(AV)} + 0.002 I_F^2(\text{RMS})$

## DYNAMIC CHARACTERISTICS (per diode)

Symbol	Parameter	Test conditions	Min.	Typ	Max.	Unit
$t_{rr}$	Reverse recovery time	$T_j = 25^{\circ}\text{C}$ $I_F = 1\text{A}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$ $V_R = 30\text{V}$		41	50	ns
$I_{RM}$	Reverse recovery current	$T_j = 125^{\circ}\text{C}$ $I_F = 100\text{A}$ $V_R = 160\text{V}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$		11.5	15	A
$t_{fr}$	Forward recovery time	$T_j = 25^{\circ}\text{C}$ $I_F = 100\text{A}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$ $V_{FR} = 1.1 \times V_{Fmax}$			800	ns
$V_{FP}$	Forward recovery voltage	$T_j = 25^{\circ}\text{C}$ $I_F = 100\text{A}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$		2.5		V

Fig. 1: Peak current versus duty cycle (per diode).




Fig. 2-2: Forward voltage drop versus forward current (maximum values, per diode).




Fig. 4: Junction capacitance versus reverse voltage applied (typical values, per diode).




Fig. 2-1: Forward voltage drop versus forward current (typical values, per diode).




Fig. 3: Relative variation of thermal impedance junction to case versus pulse duration.







Fig. 5: Reverse recovery charges versus di/dt (typical values, per diode).




**Fig. 6:** Reverse recovery time versus  $di_F/dt$  (typical values, per diode).



**Fig. 7:** Peak reverse recovery current versus  $di_F/dt$  (typical values, per diode).



**Fig. 8:** Dynamic parameters versus junction temperature.



# STTH20002TV

## PACKAGE MECHANICAL DATA ISOTOP

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	11.80	12.20	0.465	0.480
A1	8.90	9.10	0.350	0.358
B	7.8	8.20	0.307	0.323
C	0.75	0.85	0.030	0.033
C2	1.95	2.05	0.077	0.081
D	37.80	38.20	1.488	1.504
D1	31.50	31.70	1.240	1.248
E	25.15	25.50	0.990	1.004
E1	23.85	24.15	0.939	0.951
E2	24.80 typ.		0.976 typ.	
G	14.90	15.10	0.587	0.594
G1	12.60	12.80	0.496	0.504
G2	3.50	4.30	0.138	0.169
F	4.10	4.30	0.161	0.169
F1	4.60	5.00	0.181	0.197
P	4.00	4.30	0.157	0.69
P1	4.00	4.40	0.157	0.173
S	30.10	30.30	1.185	1.193

## ORDERING INFORMATION

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STTH20002TV1	STTH20002TV1	ISOTOP	27 g (without screws)	10 (with screws)	Tube

- Epoxy meets UL94, V0
- Cooling method: by conduction (C)

## REVISION HISTORY

Table 1: Revision history

Date	Revision	Description of Changes
26-May-2004	1	First issue
13-Jul-2004	2	Figure 6 legend corrected: "Forward" changed to "Reverse"

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.  
All other names are the property of their respective owners

© 2004 STMicroelectronics - All rights reserved

### STMicroelectronics GROUP OF COMPANIES

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States

www.st.com

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics:](#)

[STTH20002TV1](#)