

THINNER 2

4352-LIQUID

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Thinner 2**SDS Code:** 4352-Liquid**Related Part #** 4352-1L, 4352-4L, 4352-20L, 4352-200L

Recommended Use and Restriction on Use

Use: Coating and paint thinner and remover**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number



For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidentsUSA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300****For emergencies involving dangerous goods;** Collect 24/7CANADA: Call CANUTEC ☎: **+1-613-996-6666** or ***666** on cellular phones

THINNER 2
4352-LIQUID
Section 2: Hazard(s) Identification
Classification of Hazardous Chemical
GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	3	Warning	Flame
Eye Irritation	2A	Warning	Exclamation
Skin Irritation	2	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H226: Flammable liquid and vapor
	H315: Causes skin irritation H319: Causes serious eye irritation H336: May cause drowsiness and dizziness
Prevention	Precautionary Statements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapors/spray.

Section continued on the next page

THINNER 2
4352-LIQUID

Continued...

Prevention	Precautionary Statements
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P264	Wash hands thoroughly after handling.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, water fog, or chemical foam to extinguish.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water or shower.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
Storage	Precautionary Statements
P403 + P235	Store in well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	<i>None</i>	<i>None</i>

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
123-86-4	n-butyl acetate	100%

THINNER 2**4352-LIQUID****Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>severe irritation, redness, pain</i>
Response	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
IF ON SKIN (or hair)	P303 + P361 + P353, P332 + P313
Immediate Symptoms	<i>irritation, dry skin</i>
Response	Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water or shower. If skin irritation occurs: Get medical advice/attention.
IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>cough, sore throat, drowsiness, dizziness, headache</i>
Response	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>irritation, nausea</i>
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO, CO ₂).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

THINNER 2**4352-LIQUID****Section 6: Accidental Release Measures**

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the mist/vapors/spray. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment	Contain with inert absorbent (such as soil, sand, vermiculite).
Cleaning	Collect the liquid in a sealable, solvent-resistant container with an electrically protected vacuum cleaner, chemical absorbent, or chemical spill pad. RECOMMENDATION: Use a grounded stainless steel or carbon steel container.
Disposal	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Avoid breathing mist/vapors/spray. Use only outdoors or in well-ventilated area. In cases of inadequate ventilation wear respiratory protection.
Handling	Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling.
Storage	Keep container tightly closed. Store in a well-ventilated area. Keep cool. Store locked up.

THINNER 2
4352-LIQUID
Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
n-butyl acetate	ACGIH	150 ppm	200 ppm
	U.S.A. OSHA PEL	150 ppm	Not established
	Canada AB	150 ppm	200 ppm
	Canada BC	20 ppm	Not established
	Canada ON	150 ppm	200 ppm
	Canada QC	150 ppm	200 ppm

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS² database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection For incidental contacts, use disposable nitrile, neoprene, or other chemically resistant gloves.

Respiratory Protection For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges and particulate filter.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

Section continued on the next page

THINNER 2
4352-LIQUID
General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	1.4%
Appearance	Clear	Upper Flammability Limit	7.6%
Odor	Sweet, ester-like	Vapor Pressure @20 °C	1.33 kPa [10 mmHg]
Odor Threshold	0.04 ppm	Vapor Density	4.0 (Air = 1)
pH	Not available	Specific Gravity @25 °C	0.887
Freezing/Melting Point	Not available	Solubility in Water	Not available
Boiling Point	125 °C [257 °F]	Partition Coefficient	Not available
Flash Point ^{a)}	27 °C [81 °F]	Auto-ignition Temperature	407 °C [765 °F]
Evaporation Rate	1.0 (ButAc = 1)	Decomposition Temperature	Not available
Flammability (solid, gas)	Not available	Viscosity @40 °C	<20.5 mm ² /s

a) Tag closed cup

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, excessive heat, and incompatible substances. Vapors may form explosive mixture with air.
Incompatibilities	strong oxidizing agents, strong acids, strong bases
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

THINNER 2
4352-LIQUID
Section 11: Toxicological Information
Routes of Entry

Eye contact, Skin contact, Inhalation, and Ingestion

Symptoms Summary

Eyes	Causes severe irritation, redness, and pain.
Skin	Causes skin irritation and dry skin.
Inhalation	May cause cough, sore throat, drowsiness, dizziness, and headaches.
Ingestion	May cause irritation and nausea.
Chronic	Prolonged or repeated exposure may cause skin dryness and cracking, defat skin, and local redness and discomfort.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
n-butyl acetate	>10 768 mg/kg Rat	>17 600 mg/kg Rabbit	390 ppm 4 h Rat

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier (M)SDS were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes severe eye irritation.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.

Section continued on the next page

THINNER 2**4352-LIQUID**

Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Inhalation of n-butyl acetate may affect the central nervous system and may cause drowsiness, dizziness, and narcotic effects
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The n-butyl acetate ingredient is an acute category 3 environmental toxicant liquid (biodegradable, with minimal LC50 of 18 mg/L for fathead minnow).

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

The content is rapidly biodegradable.

Biological Oxygen Demand (BOD-5) = 730 mg/g

Chemical Oxygen Demand (COD) = 1 010 mg/g

BOD/COD ratio = 0.72

Other Effects

Volatile Organic Compound (VOC) content = 100% [887 g/L]

THINNER 2

4352-LIQUID

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); USA DOT 49 CFR (Parts 100 to 185) Regulations.

Sizes 5 L and under

Limited Quantity



Sizes greater than 5 L

UN number: UN1123
Shipping Name: BUTYL ACETATES
Class: 3
Packing Group: III
Marine Pollutant: No
Flash Point = 27 °C [81 °F]



Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes up to 60 L (passenger), 220 L (cargo)

UN number: UN1123
Shipping Name: BUTYL ACETATES
Class: 3
Packing Group: III
Marine Pollutant: No
Flash Point = 27 °C [81 °F]



Sea

Refer to IMDG regulations.

Sizes 5 L and under

Limited Quantity



Sizes greater than 5 L

UN number: UN1123
Shipping Name: BUTYL ACETATES
Class: 3
Packing Group: III
Marine Pollutant: No
Flash Point = 27 °C [81 °F]



Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

THINNER 2

4352-LIQUID

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


USA

Other Classifications

HMIS® RATING

HEALTH:	* 2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains n-butyl acetate (CAS# 123-86-4), which is subject to the CERCLA reporting requirements at the 5 000 lb (2 268 kg) threshold.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product does not contain any of the listed substances.

Section continued on the next page

THINNER 2**4352-LIQUID****SCAQMD Rule 1143** (California South Coast District)

Within the boundaries of the South Coast Air Quality Management District (in California), this product is for commercial and industrial use only, and must not be displayed for retail sale to consumers.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by	Michel Hachey
Date of Revision	17 February 2017
Supersedes	01 June 2016
Reason for Changes:	Classified to meet both HCS2012 and WHMIS 2015 regulations.

References

- 1) ACGIH *2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices*, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

THINNER 2**4352-LIQUID**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.