

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**

# Safety Data Sheet

**Section 1: Identification****Product Identifier and Other Means of Identification****Product Name:** Translucent Epoxy Encapsulating and Potting Compound**SDS Code:** 832C-Part B**Related Part #** 832C-375ML, 832C-3L, 832C-60L, 8320-125ML, 8320-1L, 8320-20L**Recommended Use and Restriction on Use****Use:** Epoxy hardener for use with resins**Uses Advised Against:** Not for use as a spray coating**Details of Manufacturer or Importer****Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)**Emergency Phone Number****For hazardous material incidents ONLY**—leaks, spills, fires, exposures or accidentsUSA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300****For emergencies involving dangerous goods;** Collect 24/7CANADA: Call CANUTEC ☎: **+1-613-996-6666** or **\*666** on cellular phones


**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**
**Section 2: Hazard(s) Identification**
**Classification of the Chemical Material**
**GHS Categories**

Criteria		Category	Signal Word	Pictograms
Serious Eye Damage		1	Danger	Corrosion
Skin Corrosion		1B	Danger	Corrosion
Sensitization	Skin sensitizer	1	Warning	Exclamation
Acute Toxicity	Dermal	4	Warning	Exclamation
Environmental Hazard	Chronic Aqua. Tox.	2	<i>none</i>	Environment
Environmental Hazard	Acute Aqua. Tox.	2	<i>none</i>	<i>none</i>

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Other Classifications**
**HMIS® RATING**

<b>HEALTH:</b>	<b>* 3</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	




**NFPA® 704 CODES**


*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

*Section continued on the next page*

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**
**Label Elements**

<b>Signal Word</b>	<b>DANGER</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H314: Causes severe skin burns and eye damage
	H312: Harmful in contact with skin H317: May cause an allergic skin reaction
	H411: Toxic to aquatic life with long lasting effects
<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P260	Do not breathe fumes/mist/vapors.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.

*Section continued on the next page*

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**

Continued...

<b>Response</b>	<b>Precautionary Statements</b>
P305 + P351 + P338, P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P303 + P361 + P353, P310	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Immediately call a POISON CENTER/doctor
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P301 + P330 + P331, P310	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.
P304 + P340, P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P391	Collect spillage.
<b>Storage</b>	<b>Precautionary Statements</b>
P405	Store locked up.
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents/container in accordance to local/regional/international regulations.

**Hazards Not Otherwise Classified**

None known

**Section 3: Composition/Information on Ingredients**

<b>CAS #</b>	<b>Chemical Name</b>	<b>%(weight)</b>
68410-23-1	fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	88%
112-24-3	triethylenetetramine	12%

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**
**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
<b>IF IN EYES</b>	P305 + P351 + P338, P310
<b>Immediate Symptoms</b>	<i>redness, severe irritation, pain, burns</i>
<b>Response</b>	Rinse cautiously with water for 30 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing.  Immediately call a POISON CENTER/doctor.
<b>IF ON SKIN (or hair)</b>	P303 + P361+ P353, P310, P333 + P313, P363
<b>Immediate or Delayed Symptoms</b>	<i>redness, irritation, rash (allergic contact dermatitis), pain, chemical burns, blistering</i>
<b>Response</b>	Take off immediately all contaminated clothing. Wash with plenty of water [shower].  Immediately call a POISON CENTRE/doctor.  If skin irritation or rash occurs: Get medical advice/attention.  Wash contaminated clothing before reuse.
<b>IF INHALED</b>	P304 + P340, P310
<b>Immediate Symptoms</b>	<i>cough, irritation of the respiratory track, burning sensation</i>
<b>Delayed Symptoms</b>	<i>asthma, difficulty breathing</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing.  Immediately call a POISON CENTER/doctor.
<b>IF SWALLOWED</b>	P301 + P330 + P331, P310
<b>Immediate Symptoms</b>	<i>Irritation, abdominal pain, nausea, vomiting, burns to the digestive tract</i>
<b>Response</b>	Rinse mouth. Do not induce vomiting.  Immediately call a POISON CENTER/doctor.

**Advice to Physicians**

In case of exposure to nitrogen oxides (NOx) combustion products or triethylenetetramine vapors during a fire, the symptoms may be delayed. For significant exposures, the exposed person should be kept under medical surveillance for 48 hours.

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B****Section 5: Fire-Fighting Measures**

<b>In case of fire</b>	P370 + P378
<b>Extinguishing Media</b>	Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish. Use water spray to cool containers.
<b>Specific Hazards</b>	<p>Not flammable or combustible, but burns if involved in a fire. Produces irritating and toxic fumes in fires or in contact with hot surfaces.</p> <p>Inhalation of toxic smoke during fire may have delayed effects. Exposed person may need to be put under surveillance for 48 h.</p> <p>Toxic for aquatic environment: Prevent fire-fighting wash from entering waterway or sewer system.</p>
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ) and nitrogen oxides (NO <sub>x</sub> ).
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	Use personal protection recommended in Section 8.
<b>Precautions for Response</b>	Avoid breathing the fumes/mist/vapors.
<b>Environmental Precautions</b>	Avoid releasing to the environment. Prevent spill from entering drains and waterways. Do not flush to sewer.
<b>Containment Methods</b>	Contain with inert absorbent (such as soil, sand, vermiculite).
<b>Cleaning Methods</b>	Collect liquid in a sealable container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe residue with a paper towel wetted with a suitable organic solvent such as alcohol or ethyl lactate, and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose spill waste according to Section 13.

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**
**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children. Avoid breathing fumes/mist/vapors or contact with skin or eyes. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink, or smoke when using this product. Avoid release to the environment.
<b>Handling</b>	Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage.
<b>Storage</b>	Store locked up.

**Section 8: Exposure Controls/Personal Protection**
**Routes of Entry**

Eye Contact, Skin Contact, Inhalation, Ingestion

**Substances with Occupational Exposure Limit Values**

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
triethylenetetramine	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	U.S.A (WEEL)	1 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	0.5 mg/m <sup>3</sup> (Skin) <sup>a)</sup>	Not established
	Canada QC	Not established	Not established

*Note:* The ACGIH<sup>1</sup>, OSHA, and Canadian provinces exposure limits were consulted. Limits from by RTECS database<sup>2</sup> of the Canadian Centre for Occupational Health and Safety (CCOHS) a data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.  
 a) Skin—can be absorbed through the skin.

*Section continued on the next page*

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B****Engineering Controls****Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

Due to low vapor pressure of the product, general ventilation should be adequate for normal use. If the product is heated at high temperatures or worker is allergic, use local ventilation and consider using a full mask with organic vapor cartridges.

**Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection (side shields).

**Skin Protection**

For likely contacts, use of protective butyl rubber, neoprene, or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection**

For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

**RECOMMENDATION:** Consult your local safety supply store to ensure your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in section 3 of this SDS, and that the respirator is fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands with water and soap after use.



**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Lower Flammability Limit</b>	Not available
<b>Appearance</b>	Clear, amber	<b>Upper Flammability Limit</b>	Not available
<b>Odor</b>	Ammonia-like	<b>Vapor Pressure @20 °C<sup>b)</sup></b>	<0.001 kPa [<0.01 mmHg]
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	>5 (Air = 1)
<b>pH</b>	Not available	<b>Specific Gravity @25 °C</b>	0.96
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Slightly soluble
<b>Boiling Point</b>	Not available	<b>Partition Coefficient</b>	Not available
<b>Flash Point</b>	>122 °C [>252 °F]	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability (solid, gas)</b>	Not available	<b>Viscosity @25 °C</b>	6 000 mm <sup>2</sup> /s

a) Component with the lowest closed cup value—triethylenetetramine

b) Literature value for triethylenetetramine

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B****Section 10: Stability and Reactivity**

<b>Reactivity</b>	Reacts exothermically with ketones, halogenated hydrocarbons, cyanides, nitriles, and epoxides. May attack metals such as aluminum, zinc, copper, and their alloys.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Avoid excessive heat and incompatible substances. Do not use in a way that forms a mist or aerosolize the product.
<b>Incompatibilities</b>	Strong oxidizing agents, strong acids
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	For thermal decomposition, see combustion products in Section 5

**Section 11: Toxicological Information****Routes of Exposure**

Eye Contact, Skin contact, Inhalation, and Ingestion

**Symptoms Summary**

<b>Eyes</b>	May causes redness, severe eye irritation, pain, or corrosive eye damage.
<b>Skin</b>	May cause redness, serious skin irritation, allergic contact dermatitis, and chemical burns. Triethylenetetramine can be absorbed through skin leading to toxic effects.  When heated, hot triethylenetetramine vapors may also result in itching of the face with skin redness (erythema) and swelling (edema).
<b>Inhalation</b>	Inhalation of vapors or mist may cause irritation to the nose, throat and lung (upper respiratory tract).
<b>Ingestion</b>	May cause severe irritation or corrosive burns to the mouth, throat, esophagus, and stomach. May cause allergic reactions. (See inhalation symptoms.)
<b>Chronic</b>	Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

*Section continued on the next page*

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**
**Lethal Exposure Concentrations**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	>5 000 mg/kg <sup>a)</sup>	>5 000 mg/kg <sup>a)</sup>	Not available
triethylenetetramine	2 500 mg/kg Rat	805 mg/kg Rabbit	Not available

*Note:* Representative toxicity data from by RTECS database<sup>2</sup> of the Canadian Centre for Occupational Health and Safety (CCOHS) data from supplier (M)SDS were also consulted.

a) Supplier MSDS

**Other Toxicological Effects**

<b>Skin corrosion/irritation</b>	Triethylenetetramine (CAS# 112-24-3) causes skin burns.
<b>Serious eye damage/irritation</b>	Triethylenetetramine (CAS# 112-24-3) causes severe eye damage.
<b>Respiratory and skin sensitization</b> (allergic reactions)	The epoxy hardener components (CAS# 68410-23-1, and 112-24-3) may cause skin sensitization according to animal studies.
<b>Carcinogenicity</b> (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
<b>Mutagenicity</b> (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
<b>Reproductive Toxicity</b> (risk to sex functions)	Based on available data, the classification criteria are not met.
<b>Teratogenicity</b> (risk of fetus malformation)	Based on available data, the classification criteria are not met.
<b>STOT-single exposure</b>	Based on available data, the classification criteria are not met.
<b>STOT-repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met. There is no category 1 components, and the kinematic viscosity is >20.5 mm <sup>2</sup> /s at 40 °C.

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B****Section 12: Ecological Information**

The IMDG Code criteria and the raw-material (M)SDS along with supporting data for the classification of registered substances from the European Chemical Agency database (<http://echa.europa.eu>) were used.

The fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines (CAS# 68410-23-1) were classified as a chronic category 2 environmental toxicant (not readily biodegradable, LC50 range of 1–10 mg/L for fish; EC0 bacterial >10 and ≤100 mg/L).

Literature values for the triethylenetetramine (CAS # 112-24-3) suggest an acute category 3 aquatic toxicity (LC50, IC50, and EC50 values of >100 mg/L for fish and between 10 and 100 mg/L for algae).

**Acute Ecotoxicity**

Category 2

H401: Toxic to aquatic life

**Chronic Ecotoxicity**

Category 2

H411: Toxic to aquatic life with long lasting effect

Avoid release to the environment.

**Biodegradability**

Not readily biodegradable

**Bioaccumulation**

Not available

**Other Effects**

Not available

**Section 13: Disposal Considerations**

Dispose of contents in accordance with all local, provincial, state, and federal regulations.

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**
**Section 14: Transport Information**
**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes 1 L and under

**Limited Quantity**

**Note:** The 832C-375ML and 832C-3L kits are composed of separate containers which meet this inner packaging limit.



Sizes greater than 1 L

**UN number:** UN2259

**Shipping Name:**

TRIETHYLENETETRAMINE SOLUTION, N.O.S. (containing dimer fatty acid (C18)poly amido amine resin)

**Class:** 8

**Packing Group:** II

**Marine Pollutant:** Yes


**Air**

**Refer to ICAO-IATA Dangerous Goods Regulations.**

Sizes 0.5 L and under

**Limited Quantity**



Sizes greater than 0.5 L up to 1 L

**UN number:** UN2259

**Shipping Name:**

TRIETHYLENETETRAMINE SOLUTION, N.O.S. (containing dimer fatty acid (C18)poly amido amine resin)

**Class:** 8

**Packing Group:** II

**Marine Pollutant:** Yes



**Excepted Quantity E2 ≤30 mL**

*Section continued on the next page*

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B**
**Sea**

Refer to IMDG regulations.	
Sizes 1 L and under  <b>Limited Quantity</b> <b>Note:</b> The 832C-375ML and 832C-3L kits are composed of separate containers which meet this inner packaging limit.	Sizes greater than 1 L  <b>UN number:</b> UN2259 <b>Shipping Name:</b> TRIETHYLENETETRAMINE SOLUTION, N.O.S. (containing dimer fatty acid (C18)poly amido amine resin) <b>Class:</b> 8 <b>Packing Group:</b> II <b>Marine Pollutant:</b> Yes



**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**Section 15: Regulatory Information**
**Canada**
**WHMIS Classification**


E – Corrosive (Chemical burns); D1B – Toxic (Skin Absorption);  
 D2B – Toxic Other (Skin Sensitizer)

**Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.

**Industry and Science Canada**

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

**Health Canada**

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

*Section continued on the next page*

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B****USA****CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, Sept 2, 2011 revision, USA).

This product does not contain any listed substances in California.

**Europe****RoHS**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

**WEEE**

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

**SDS Prepared by** Michel Hachey

**Date of Revision** 28 May 2015

**Supersedes** 14 August 2013

**Reason for Changes:** Change to better meet HCS 2012 and WHMIS 2015 requirements.

**Reference**

1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

*Section continued on the next page*

**TRANSLUCENT EPOXY ENCAPSULATING AND POTTING COMPOUND 832C-PART B****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer** This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.