


Features

- Surface Mount
- Typical Coupling +10dB
- 260°C compatible
- RoHS Compliant
- Available on Tape and Reel
- Pb Free

Description

MACPCT0040 is a 10 dB broadband Coupler in a low cost, surface mount package. It offers low loss, good isolation, good input/output matching and exceptional coupling repeatability. Ideally suited for high volume CATV/Broadband applications.

Functional Schematic



Pin Configuration

Pin No.	Function
1	Input
2	Ground
3	Coupled
4	Isolated (external 50 Ω termination)
5	Output

Electrical Specifications: $T_A = 25^\circ\text{C}$, $Z_0 = 50 \Omega$

Parameter	Test Conditions	Units	Min	Typ	Max
Coupling	5 - 500 MHz	dB	—	9.95	10 ± 0.4
	500 - 1000 MHz			9.90	10 ± 0.6
Main Line Loss	5 - 500 MHz	dB	—	1.1	1.4
	500 - 1000 MHz			1.3	1.7
Directivity	5 - 50 MHz	dB	20	22	—
	50 - 500 MHz		18	21	
	500 - 1000 MHz		13	18	
Input Return Loss	5 - 1000 MHz	dB	16	21	—
Output Return Loss	5 - 50 MHz	dB	20	30	—
	50 - 500 MHz		28	40	
	500 - 1000 MHz		20	35	
Coupling Return Loss	5 - 500 MHz	dB	16	20	—
	500 - 1000 MHz		13	18	
Isolation Return Loss	5 - 50 MHz	dB	20	30	—
	50 - 500 MHz		25	43	
	500 - 1000 MHz		16	25	

Ordering Information


Part Number	Package
MACPCT0040TR	2000 piece reel

Absolute Maximum Ratings


Parameter	Absolute Maximum
Input Power	250 mW
DC Current	30 mA
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

Typical Performance Curves: $T_A = +25^\circ\text{C}$, $Z_0 = 50 \Omega^1$


Coupling




Main Line Loss




Directivity




Input Return Loss



Output Return Loss




Coupling Return Loss



1. Full Temperature Plots Available on request.

Dimensions



1. Dimensions in mm
2. Tolerance: ± 0.2 mm unless otherwise noted
3. Model number and lot code are printed on reel
4. Lead Finish: Gold

Tape & Reel Information

Parameter	Units	Value
Qty Per Reel	-	2000
Reel Size	mm	330
Tape Width	mm	12.00
Pitch	mm	8.00
Orientation	-	F5
Reference Application Note ANI-019 for orientation		

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.